


CROWN LINK[®]

專業薄膜開關連接器第一品牌

RoHS



section B-B



0T:TIN PLATED

◆ SPECIFICATIONS

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 3 AMP

DIELECTRIC WITHSTANDING VOLTAGE:

AC 250V FOR 1 MINUTE

INSULATION RESISTANCE: 500 MΩ

◆ ENVIRONMENTAL

TEMPERATURE RANGE: -40°C~+105°C

◆ PART NO.

2812 - 30K - 0T -ML

SERIES NO.

30K/REEL

MALE

0T:TIN PLATED

OTHER PLATINGS ON REQUEST

				X. ±0.2
				.X ±0.1
A	FIRST DRAWING	TRACY	2015.11.23	.XX ±0.05
REV//版本	MODIFIED CONTENT /變更內容	DRAWN/繪圖	DATE/日期	TOLERANCE RANGE/公差範圍

DRAWN/繪圖	DATE/日期	CROWN LINK[®] THE LEADING MANUFACTURER OF FPC & FFC CONNECTOR, HOUSING AND DOME.			
TRACY	2015.11.23	PRODUCT NAME/品名			
CHECK BY/審查	DATE/日期	2.54mm PITCH FFC/FPC CONNECTOR			
VIVIAN	2015.11.23	PART NO./料號	SCALE/比例	SIZE/圖號	UNIT/單位
APPROVED BY/核准	DATE/日期	2812-30K-0T-ML	4:1	A4	mm
JASON	2015.11.23	MATERIAL/材質	ANGLE OF VIEW/視角	SHEET/頁碼	REV//版本
PACKAGE/包裝	30,000PCS/REEL	PHOSPHOR BRONZE		1 OF 1	A