

4



3

2

1

CROWN LINK[®]

專業薄膜開關連接器第一品牌

ROHS**◆ SPECIFICATIONS**

TRIP FORCE: 200 ± 30 g

CLICK RATIO: MIN 40 %

◆ TESTING CONDITIONS

FORCE TEST PROBE: HARD POINTED

LIFE TEST PROBE: RB 60° SILICON ROUND HEAD

LIFE TEST FORCE: 255 g

LIFE TEST SPEED: 180 CYCLE / MIN

BURR: MAX 0.05 MM

UNLESS OTHERWISE SPECIFIED TESTING METHOD
ACCORDING TO CROWNLINK STANDARD PROCEDURE**SECTION A-A**

				X.XX ±0.10
A	FIRST DRAWING	ANNIE	2013.08.15	TOLERANCE RANGE/公差範圍
REV/版本	MODIFIED CONTENT /變更內容	DRAWN/繪圖	DATE/日期	

DRAWN/繪圖	DATE/日期	CROWN LINK[®] THE LEADING MANUFACTURER OF FPC & FFC CONNECTOR, HOUSING AND DOME.						
CHECK BY/審查	DATE/日期	PRODUCT NAME/品名						
APPROVED BY/核准	DATE/日期	METAL DOME						
PACKAGE/包裝	DATE/日期	PART NO./料號	THICKNESS/厚度	SCALE/比例	SIZE/圖號	UNIT/單位		
		CL12-TND-200T	0.12 mm	18:1	A4	mm		
		MATERIAL/材質			ANGLE OF VIEW/視角	SHEET/頁碼	REV/版本	
		DOUBLE SIDE NICKEL PLATED						
		STAINLESS STEEL SUS 304						