

4



3

2

1

CROWN LINK[®]

專業薄膜開關連接器第一品牌

ROHS**SECTION A-A****◆ SPECIFICATIONS**

TRIP FORCE: 280 ± 30 g

CLICK RATIO: MIN 35 %

◆ TESTING CONDITIONS

FORCE TEST PROBE: HARD POINTED

LIFE TEST PROBE: RB 60° SILICON ROUND HEAD

LIFE TEST FORCE: 340 g

LIFE TEST SPEED: 180 CYCLE / MIN

BURR: MAX 0.05 MM

UNLESS OTHERWISE SPECIFIED TESTING METHOD
ACCORDING TO CROWNLINK STANDARD PROCEDURE

				X.XX ±0.10
B	NEW DRAWING FORMAT & REVISE DIMPLE DEPTH	ANNIE	2013.12.28	
A	FIRST DRAWING	ANNIE	2004.02.20	
REV/版本	MODIFIED CONTENT /變更內容	DRAWN/繪圖	DATE/日期	
				TOLERANCE RANGE/公差範圍

DRAWN/繪圖	DATE/日期	THE LEADING MANUFACTURER OF FPC & FFC CONNECTOR,HOUSING AND DOME.				
ANNIE	2013.12.28	CROWN LINK[®]				
CHECK BY/審查	DATE/日期					
VIVIAN	2013.12.28	PRODUCT NAME/品名 METAL DOME				
APPROVED BY/核准	DATE/日期	PART NO./料號	THICKNESS/厚度	SCALE/比例	SIZE/圖號	UNIT/單位
JASON	2013.12.28	CL12-RWDS-280T	0.12 mm	8:1	A4	mm
PACKAGE/包裝	10,000PCS/BAG	MATERIAL/材質		ANGLE OF VIEW/視角	SHEET/頁碼	REV/版本
		STAINLESS STEEL SUS 304			1 OF 1	B