

4

3

2

1

CROWN LINK[®]

專業薄膜開關連接器第一品牌

ROHS1.4 3X
A

Ø7.0

A

0.59 B

**◆ SPECIFICATIONS**

TRIP FORCE: 750 ± 30 g

CLICK RATIO: MIN 30 %

◆ TESTING CONDITIONS

FORCE TEST PROBE: HARD POINTED

LIFE TEST PROBE: RB 60° SILICON ROUND HEAD

LIFE TEST FORCE: 860 g

LIFE TEST SPEED: 180 CYCLE / MIN

BURR: MAX 0.05 MM

UNLESS OTHERWISE SPECIFIED TESTING METHOD
ACCORDING TO CROWN LINK STANDARD PROCEDURE**SECTION-A-A**

C	NEW DRAWING FORMAT & CORRECT DIMPLE DEPTH	ANNIE	2013.04.12	X.XX ±0.10
B	CONVERT TO NEW DRAWING & REVISE DOME HEIGHT	ANNIE	2012.10.19	
A	FIRST DRAWING	ANNIE	2004.02.20	
REV/版本	MODIFIED CONTENT /變更內容	DRAWN/繪圖	DATE/日期	
				TOLERANCE RANGE/公差範圍

DRAWN/繪圖	DATE/日期	CROWN LINK[®] THE LEADING MANUFACTURER OF FPC & FFC CONNECTOR, HOUSING AND DOME.				
ANNIE	2013.04.12	PRODUCT NAME/品名				
CHECK BY/審查	DATE/日期	METAL DOME				
VIVIAN	2013.04.12	PART NO./料號	THICKNESS/厚度	SCALE/比例	SIZE/圖號	UNIT/單位
APPROVED BY/核准	DATE/日期	CL7-RWDSD-750T	0.10 mm	16:1	A4	mm
JASON	2013.04.12	MATERIAL/材質	ANGLE OF VIEW/視角	SHEET/頁碼	REV/版本	
PACKAGE/包裝	10,000PCS/BAG	STAINLESS STEEL SUS 304	1 OF 1			