

4



3

2

1

CROWN LINK[®]

專業薄膜開關連接器第一品牌

ROHS

SECTION A-A



◆ SPECIFICATIONS

TRIP FORCE: 450 ± 30 g

CLICK RATIO: MIN 45 %

◆ TESTING CONDITIONS

FORCE TEST PROBE: HARD POINTED

LIFE TEST PROBE: RB 60° SILICON ROUND HEAD

LIFE TEST FORCE: 530 g

LIFE TEST SPEED: 180 CYCLE / MIN

BURR: MAX 0.05 MM

UNLESS OTHERWISE SPECIFIED TESTING METHOD

ACCORDING TO CROWN LINK STANDARD PROCEDURE

C	NEW DRAWING FORMAT	ANNIE	2013.01.02	X.XX ±0.10
B	CONVERT TO NEW DRAWING FORMAT	ANNIE	2005.07.14	
A	FIRST DRAWING	ANNIE	2004.06.07	
REV/版本	MODIFIED CONTENT /變更內容	DRAWN/繪圖	DATE/日期	TOLERANCE RANGE/公差範圍

DRAWN/繪圖	DATE/日期	CROWN LINK[®] THE LEADING MANUFACTURER OF FPC & FFC CONNECTOR, HOUSING AND DOME.				
ANNIE	2014.01.03	PRODUCT NAME/品名				
CHECK BY/審查	DATE/日期	METAL DOME				
VIVIAN	2014.01.03	PART NO./料號	THICKNESS/厚度	SCALE/比例	SIZE/圖號	UNIT/單位
APPROVED BY/核准	DATE/日期	CL8-RWDSD-450T	0.08 mm	10:1	A4	mm
JASON	2014.01.03	MATERIAL/材質	ANGLE OF VIEW/視角	SHEET/頁碼	REV/版本	
PACKAGE/包裝	10,000PCS/BAG	STAINLESS STEEL SUS 304		1 OF 1	C	